



MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30

Product #959

API SN-RC/ILSAC GF-5



Available in 5 Gal, 55 Gal, Bulk

Size	Product Code
5 Gal	959-05
55 Gal	959-55
Bulk	959-Bulk

MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30 is the premium choice oil for maintaining and prolonging the life of your high mileage engine. MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30 is formulated with an additive package that specifically targets issues in engines with over 75,000 miles.

Where standard engine oils are formulated for new engines, MINNOCO High Mileage was developed for old engines that experience oil leaks, oil consumption, loss of power and performance, spark plug fouling, excessive intake valve deposits and sludge build-up. MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30 contains seal conditioning agents for reducing leaks, and premium additives for improved wear protection and reduced oil consumption.

MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30 is suitable for use in new and high-mileage, gasoline-fueled and flex-fueled passenger cars, light trucks, powerboats, and other stationary equipment.

MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30, is licensed to meet or exceed the latest automotive manufacturers' requirements API SN and SN-RC (Resource Conserving) and ILSAC GF-5 standards.

Features & Benefits

- Conditions engine seals for reduced leaks
- Excellent volatility for low oil consumption
- Protects engine from wear, bearing corrosion, rust
- Advanced varnish & sludge protection
- Protects the engine from deposits at all operating temperatures
- Increased thermal stability at high temperatures

Please see page 2 for Applications and Typical Properties.

MSSA/Minnoco

2886 Middle Street, Little Canada, MN 55117

Ph: 651-487-1983 • Fax: 651-487-2447

e-mail: admin@mnsa.com



MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30

Product #959

API SN-RC/ILSAC GF-5

APPLICATIONS

MINNOCO High Mileage Synthetic Blend 5W-30 Motor Oil may be recommended in the following applications listed below. Follow equipment manufacturer recommendations for specific applications.

MINNOCO High Mileage Synthetic Blend Motor Oil 5W-30 meets or exceeds the current and previous API service classifications: API SN, SM, SL, SJ, SH, SG, SF and ILSAC GF-5, GF-4, GF-3, GF-2 & GF-1.

- May be used in both old and newer passenger car engines
- When Ford WSS-M2C946-A is specified
- When Chrysler MS-6395S is specified

For GM Vehicles model years 2011 and after, see our MINNOCO dexos1™ Full Synthetic Motor Oil.

MINNOCO HIGH MILEAGE SYNTHETIC BLEND ENGINE OIL TYPICAL PROPERTIES

SAE GRADE	5W-30
Viscosity @ 40°C, cSt	63.01
Viscosity @ 100°C, cSt	10.57
Viscosity, SUS @ 210°F	61.25
Viscosity Index	158
API Gravity	33.01
Pour Point: °C	-48
API: RC (Resource Conserving):	YES
ILSAC GF-5 Certified:	YES
API Licensed Service:	SN, SM, SL, SJ ILSAC GF-5

Typical properties are average values only and do not constitute a specification.

For recommendations on safe handling and use of this product please see the Safety Data Sheet listed on the web at www.minnoco.com. Please contact your Minnoco sales representative or visit us on the web at www.minnoco.com for additional product information.

MSSA/Minnoco

2886 Middle Street, Little Canada, MN 55117
Ph: 651-487-1983 • Fax: 651-487-2447
e-mail: admin@mnsa.com